



Technical Data Sheet

Blackfriar Anti-Slip Step Paint

Specially designed for steps, this paint contains an aggregate that helps to reduce the risk of slipping, while providing an attractive, hard-wearing finish.

Performance characteristics –

- Anti-slip - added aggregate helps reduce slipping.
- Interior and exterior use.
- Hard-wearing.

Preparation - Ensure surface to be coated is clean, dry, sound and free from wax, grease or any other contamination. Remove any loose or flaking paint back to a firm edge. Previously painted surfaces in sound condition should be abraded and degreased prior to application of Blackfriar Anti-Slip Step Paint. Blackfriar Anti-Slip Step Paint can be applied directly to bare concrete however other bare or new surfaces should be primed with the appropriate Blackfriar primer. New concrete must be left for 6 months to dry before painting. Caution should always be exercised when walking on steps, even after application of this product. Situations can arise where steps may be slippery: ie. After moss build-up, accumulation of wet leaves, heavy rainfall, liquid spillages, etc.

Application - Stir thoroughly prior to use with a broad stirrer. The product may be applied by brush or roller working the paint into any surface imperfections. Apply the material as evenly as possible to maintain an overall consistent finish. Two coats are recommended to give best protection.

Thinning - Maximum 10% white spirit.

Limitations - Do not use under cold (less than 5°C), damp or humid conditions. Not suitable for power-floated or granolithic concrete, asphalt, quarry tiles or surfaces suffering from rising damp. Slip resistance can be impaired by a build up of wet leaves, oil, ice or by ponding of water on the surface.

Coverage - Up to 14m² per litre per coat.

Drying Time - Touch dry in 4 hours. Recoat after 16 hours and within 3 days. Drying times are based on an ambient temperature of 20°C and 50% relative humidity. Lower temperatures or higher humidity will prolong the drying and overcoating times.

Clean Up - Remove as much product as possible from application equipment before washing with white spirit. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

Storage - Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight.

Warning

Contains: Naphtha (petroleum), hydrotreated heavy.

Flammable liquid and vapour.

May cause drowsiness or dizziness.

Keep out of reach of children.

Read label before use.

If medical advice is needed, have product container or label at hand.

Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

Avoid breathing vapour. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Call a doctor if you feel unwell.

Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains neodecanoic acid, cobalt salt and 2-butanone oxime. May produce an allergic reaction.

Repeated exposure may cause skin dryness or cracking.

EU limit values: 600g/l (2007) 500g/l (2010.) This product

contains a maximum of 500g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.