

BLACKFRIAR PAINTS LTD

TECHNICAL DATA SHEET

BF032 Quick Drying Metal Paint.

Revision
date:
18/12/07

<u>Product Information</u>	<u>Technical Spec</u>	<u>Recommended Spreading Rate</u>
<p><u>Description</u></p> <p>Multi purpose high gloss paint for metal and wood.</p> <p><u>Usage/purpose</u></p> <p>Ideal for factory maintenance (such as plant and machinery) vehicles, caravans, bicycles, signs, garden furniture, gates railings, garage doors etc</p> <p><u>Characteristics</u></p> <p>A high build smooth finish that is hardwearing and protective.</p> <p><u>Finish</u></p> <p>High Gloss</p> <p><u>Colour(s)</u></p> <p>White, Black, Red, Landrover Green, Grey, Blue, Yellow, Silver</p> <p><u>Packaging</u></p> <p>250ml, 500ml, 1litre, 2.5litre.</p> <p><u>Disclaimer;</u> The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements</p>	<p><u>Composition</u></p> <p>A high quality long oil alkyd resin blended with a modified rosin phenolic resin. Pigmented with lightfast pigments.</p> <p><u>Properties</u></p> <p>VOC Content: EU Limit value (Cat A/i); 500g/L This product contains maximum 500g/L</p> <p><u>Performance</u></p> <p>Tough and durable. Heat resistant to 150°C. Resistant to minor oil and grease contamination and occasional fuel splashes.</p> <p><u>Surface Preparation</u></p> <p>Ensure the substrate to be painted is sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease etc). Remove all signs of rust to a clean bright surface. Where necessary prime new and bare areas with the appropriate Blackfriar Primer</p> <p><u>Application Method</u></p> <p>Brush, Roller, Spray Ensure products are thoroughly stirred with a broad stirrer. No undercoat is necessary. Apply at least two full coats for protection purposes.</p> <p>For Technical Enquiries, Material Safety Data Sheets Telephone Sales on 0191 4113146</p>	<p>Up to 14m²/L/coat</p> <p><u>Thinning</u></p> <p>Not recommended</p> <p><u>Drying Time</u></p> <p>Touch dry in 2-4 hours Recoatable after 16 hours under normal conditions (20°C 50% r/h).</p> <p><u>Cleaning</u></p> <p>Clean application equipment or spills with white spirit or Blackfriar Brush Cleaner</p> <p><u>Limitations</u></p> <p>NB.QD90 Silver is not resistant to Petrol, Fuel Oil or brake fluid.</p> <p><u>Environmental Info.</u></p> <p>Dangerous for the environment</p> <p>Paint Product UN No. 1263.</p> <p>Tor Coatings Ltd. Portobello Industrial Est, Birtley Chester-le Street County Durham DH3 2RE</p>