



Technical Data Sheet

Blackfriar Raw Linseed Oil

Blackfriar Raw Linseed Oil penetrates deep into wood, nourishing it from within. It is ideal for oak beams, cricket bats and bean canes. It can also be used for softening glazing putty and as a lubricant for French Polish.

Performance characteristics –

- Interior and exterior use.
- Nourishes and Protects wood.
- Penetrates deep into wood.
- Suitable for most woods.

Preparation - Ensure surface to be oiled is smooth, clean, dry and free from any surface contamination. For surfaces previously treated with oils or waxes clean back the surface to bare timber with fine wire wool and white spirit, working along the grain.

Application - Ensure the product is thoroughly shaken prior to use. Apply oil liberally by brush or rag. Leave for a few minutes for the oil to absorb into the wood then wipe off any surplus. Allow the oil to dry overnight before using or recoating. When applying to new wood thin the first coat with 10% white spirit.

Thinning - Maximum 10% white spirit.

Limitations - If used on exterior projects, very regular maintenance will be required to keep the wood nourished.

Coverage - Up to 10m² per litre per coat. Will depend upon porosity of the wood.

Drying Time - Non-drying. The product is absorbed into the wood. Recoat after 12 hours.

Clean Up - Take extra care as application cloths and soiled cleaning rags may self ignite without warning. Lay cloths out flat in single layers to dry, or wash out thoroughly in warm soapy water before disposal. Remove as much

product from application equipment as possible before washing with white spirit. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

Storage - Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight.

Keep out of reach of children.

Read label before use.

If medical advice is needed, have product container or label at hand.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

EU limit values: 500g/l (2007) 400g/l (2010.) This product contains a maximum of 100g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.