



Technical Data Sheet

Blackfriar Teak Oil

Blackfriar Teak Oil protects, revives and enhances the appearance of Teak and similar hardwoods. Ideal for hardwood furniture, doors and panelling. When used regularly it will reduce the risk of wood greying, weathering and surface splitting.

Performance characteristics –

- Enhances the appearance of Teak and hardwoods.
- Replaces the natural oils lost through weathering.
- Reduces surface splitting.
- Interior and exterior use.

Preparation - Ensure surface to be oiled is smooth, clean, dry and free of contamination. For surfaces previously treated with oils or waxes clean back the surface to bare timber with fine wire wool and white spirit, working along the grain. Previously painted or varnished surfaces should be stripped back to bare using Blackfriar Professional Paint and Varnish Remover. Any French polish on surfaces must also be completely removed.

Application - Ensure the product is thoroughly shaken prior to use. Apply oil liberally by brush or rag. Leave for a few minutes for the oil to absorb into the wood then wipe off any surplus. Allow the oil to dry for 24 hours before using or recoating. When applying to new wood thin the first coat with 5% white spirit.

Thinning - Maximum 10% white spirit.

Limitations - Do not apply in wet conditions or if the temperature is below 5°C. For best results apply a minimum of three coats leaving a minimum of 24 hours between coats. Apply regularly to maintain protection of wood (at least annually).

Coverage - Up to 14m² per litre per coat. Dependant on porosity of wood.

Drying Time - Touch dry in 6 - 8 hours. Recoat after 24 hours and within 3 days. Drying times are based on an ambient temperature of 20°C and 50% relative humidity. Lower temperatures or higher humidity will prolong the drying and overcoating times.

Clean Up - Take extra care as application cloths and soiled cleaning rags may self ignite without warning. Lay cloths out flat in single layers to dry, or wash out thoroughly in warm soapy water before disposal. Remove as much product from application equipment as possible before washing with white spirit. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

Storage - Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight.

Warning

Contains: Naphtha (petroleum), hydrotreated heavy.

Flammable liquid and vapour.

May cause drowsiness or dizziness.

Keep out of reach of children.

Read label before use.

If medical advice is needed, have product container or label at hand.

Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

Avoid breathing vapour.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Call a doctor if you feel unwell.

Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains: Neodecanoic acid, cobalt salt and octhlinone (ISO). May produce an allergic reaction.

Repeated exposure may cause skin dryness or cracking.

EU limit values: 700g/l (2007) 700g/l (2010.) This product contains a maximum of 700g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.