

BLACKFRIAR PAINTS LTD

TECHNICAL DATA SHEET

Review date:
12/11/13

BF027 **Blackfriar Quick Drying Interior Varnish Clear**

<p><u>Product Information</u></p> <p><u>Description</u></p> <p>Clear quick drying water based varnishes.</p> <p><u>Usage/purpose</u></p> <p>For coating furniture, floors, doors, wooden panelling, interior joinery, skirting etc.</p> <p><u>Characteristics</u></p> <p>A smooth finish that brings out the natural beauty of wood. Low odour.</p> <p><u>Performance</u></p> <p>Hardwearing – resists knocks, boiling water, alcohol, stains and dilute acids and alkalis.</p> <p><u>Finish</u></p> <p>Available as Gloss / Satin & Matt</p> <p><u>Colour(s)</u></p> <p>Almost colourless, does not yellow with age.</p> <p><u>Packaging</u></p> <p>250ml, 500ml, 1l, 2.5l. Larger sizes may be available on request dependant on volume required</p> <p><u>Disclaimer;</u></p> <p>The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements</p>	<p><u>Technical Spec Composition</u></p> <p>Based on a high quality acrylic emulsion. Contains polyurethane.</p> <p><u>Properties</u></p> <p>VOC Content: EU Limit (cat A/e) : 130g/L This product contains max 130g/L</p> <p><u>Performance</u></p> <p>Excellent hardwearing varnish for interior use.</p> <p><u>Surface Preparation</u></p> <p>Ensure the substrate to be varnished is sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease, polish etc). If preparing a floor which, has been previously waxed polished always degrease prior to sanding. When applying to new wood thin the first coat with up to 10% water.</p> <p><u>Application Method</u></p> <p>Brush, Roller, Spray Ensure varnishes are thoroughly stirred with a broad stirrer, especially the matt and satin grades.</p> <p>For Technical Enquiries or Material Safety Data Sheets, contact Sales on 0191 4113146</p>	<p><u>Recommended Spreading Rate</u></p> <p>14m²/ltr Apply 3-4 coats for optimum performance.</p> <p><u>Thinning</u></p> <p>Up to 10% water.</p> <p><u>Drying Time</u></p> <p>Touch dry in 1 hour Recoat after 4 hours under normal conditions (20°C 50% r/h).</p> <p><u>Cleaning</u></p> <p>Clean application equipment or spills with water</p> <p><u>Limitations</u></p> <p>For interior use only. Do not use under cold (less than 10⁰ C) and or damp conditions</p> <p>Matt finish is not as durable as satin or gloss finish when used on floors.</p> <p><u>Environmental Info.</u></p> <p>Water-Based.</p> <p>Tor Coatings Ltd. Portobello Industrial Est, Birtley Chester-le Street County Durham DH3 2RE</p>
--	--	--