

BLACKFRIAR PAINTS LTD

TECHNICAL DATA SHEET

BF006 Blackfriar Super Yacht Varnish

Review date:
23/03/2010

<u>Product Information</u>	<u>Technical Spec</u>	<u>Recommended Spreading Rate</u>
<p><u>Description</u></p> <p>A durable, high performance exterior varnish with a full gloss finish.</p> <p><u>Usage/purpose</u></p> <p>Primarily for use on exterior joinery, hardwood doors and window frames.</p> <p><u>Characteristics</u></p> <p>Excellent UV resistance</p> <p><u>Finish</u></p> <p>Gloss</p> <p><u>Colour</u></p> <p>Clear (will give slight yellow hue).</p> <p><u>Packaging</u></p> <p>250ml, 500ml, 1litre, 2.5litre. Larger sizes may be available on request dependant on volume required</p> <p><u>Disclaimer;</u> The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements</p>	<p><u>Composition</u></p> <p>Long Oil Pure Phenolic Wood Oil medium modified with a specially formulated durable alkyd in low aromatic white spirits.</p> <p><u>VOC</u></p> <p>EU limit value for this product (cat A/e): 400 g/l (2010). This product contains max 400 g/l VOC</p> <p><u>Performance</u></p> <p>A weather resistant, flexible, water repelling coating for new or bare wood.</p> <p><u>Surface Preparation</u></p> <p>Ensure the substrate to be coated is sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease, polish etc). If sanding ensure all debris is removed before varnishing.</p> <p><u>Application Method</u></p> <p>Brush or Spray Ensure products are thoroughly stirred with a broad stirrer. Apply a minimum of three coats for exterior protection.</p> <p>For Technical Enquiries, Material Safety Data Sheets Telephone Sales on 0191 4106611</p>	<p>14m²/l</p> <p><u>Drying Time</u></p> <p>Touch dry in 2-4 hours Recoat after 16 hours under normal conditions (20°C 50% RH).</p> <p><u>Cleaning</u></p> <p>Clean application equipment or spills with white spirit or Blackfriar Brush Cleaner</p> <p><u>Limitations</u></p> <p>Clear varnishes are not as durable as pigmented varnishes or stains. Inspect Clear varnishes <u>regularly</u> and maintain immediately any sign of breakdown occurs.</p> <p><u>Environmental Info.</u></p> <p>Harmful to aquatic organisms. Flammable</p> <p>Paint Product UN No. 1263.</p> <p>Tor Coatings Ltd. Portobello Industrial Est, Birtley Chester-le Street County Durham DH3 2RE</p>