

## BLACKFRIAR

<b>BF013 QUICK DRY EXTERIOR WOODSTAIN</b>
<b>STAINS, PROTECTS AND TRANSFORMS EXTERIOR TIMBER. FOR HARD AND SOFT WOODS. QUICK DRYING</b>
UV PROTECTED WATER BASED TRANSLUCENT SATIN FINISH FOR HARD AND SOFT WOODS ENHANCES WEATHERED TIMBER
<p style="text-align: center;"><b>BLACKFRIAR QUICK DRY EXTERIOR WOODSTAIN</b></p> <p>Blackfriar Quick Drying Exterior Woodstain stains, protects and finishes all-in-one. Designed for all exterior timber, hard or softwood, rough or smooth. Ideal for window and door frames, cladding, fences and sheds. May be used inside on wood not exposed to heavy wear.</p>
<p><b>PREPARATION</b></p> <p>Ensure surface to be treated is clean, dry, sound and free from wax, oil or any other contamination. Bare wood should be sanded to a smooth surface, always working with the grain - do not use wire wool as this may discolour the timber. Oily woods such as Teak or Iroko should be cleaned with white spirit prior to application. Previously painted or varnished surfaces should be stripped back to bare wood using Blackfriar Professional Paint and Varnish Remover. Any excess resinous deposits around knots should be scraped off and the area cleaned with white spirit. Building regulations require that all new timber is treated with a wood preservative. Ensure new or bare timber is adequately preserved prior to applying wood finishes, apply Blackfriar Goldstar Clear Wood Preservative to untreated timbers where required.</p>
<p><b>APPLICATION</b></p> <p>Stir thoroughly prior to use. Apply a minimum of 2 coats by brush, 3 coats for clear. Apply evenly using light strokes following the grain of the wood. If the colour obtained with only one coat is suitable, finish with one coat of Blackfriar Quick Drying Exterior Woodstain Clear. If the overcoating time is exceeded, lightly abrade with fine glass paper working with the grain and remove dust. Provided the timber and coatings are in good condition, further coats of Blackfriar Quick Drying Exterior Woodstain Clear maybe applied, as and when necessary, to freshen up the finish – clean and abrade prior to the application. The woodstain will appear cloudy when wet but will quickly dry to a translucent finish. When applying to new or bare wood, the first coat may be thinned with up to 5% water to ease application.</p>
<p><b>APPEARANCE</b></p> <p>Satin Finish, Clear, Mahogany, Teak, Medium Oak &amp; Dark Oak.</p>
<p><b>COVERAGE RATE</b></p> <p>Up to 14m<sup>2</sup>/litre per coat. Dependent on porosity of wood.</p>
<p><b>DRYING TIME</b></p> <p>Touch dry in 1 - 2 hours. Recoat after 4 hours and within 3 days. Drying times are based on an ambient temperature of 20°C and 50% relative humidity. Lower temperatures or higher humidity will prolong the drying and overcoating times.</p>
<p><b>PACK SIZES</b></p> <p>1L, 500ML</p>
<p><b>CLEAN UP</b></p> <p>Remove as much product as possible from application equipment before washing with water. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.</p>
<p><b>VOC</b></p> <p>EU limit value for this product (cat A/e): 130 g/l. This product contains max 30 g/l VOC</p>
<p><b>LIMITATIONS</b></p> <p>Do not apply in cold, damp or humid conditions (less than 10°C). The final shade of the product depends upon the original colour and absorbency of the wood. We recommend to test for shade on an off-cut or inconspicuous area. For a clear finish on smooth, new timber, Blackfriar Quick Drying Exterior Woodstain Clear may be used with a minimum of 3 coats. Clear coats are not as durable as coloured finishes and will require more regular maintenance. Application of Blackfriar UV Wood Primer prior to the Quick Drying Exterior Woodstain will prolong the life of the coating especially for the clear.</p>
<p><b>DISCLAIMER</b></p> <p>The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.</p>
<p>Tor Coatings Ltd, Portobello Industrial Estate, Birtley, Chester-le-Street, County Durham, DH3 2RE.            For Technical Enquiries or Material Safety Data Sheets. Contact sales on 0191 410 6611.</p>