

BLACKFRIAR

| |
|--|
| BF0771001 DANISH OIL |
| NOURISHES AND PROTECTS HARD AND SOFT WOODS. BRINGS OUT THE NATURAL GRAIN. INTERIOR / EXTERIOR |
| INTERIOR / EXTERIOR USE SATIN FINISH PENETRATES DEEP INTO WOOD NOURISHES AND PROTECTS WOOD FOR ALL HARD AND SOFT WOODS |
| BLACKFRIAR DANISH OIL Blackfriar Danish Oil penetrates deep into the wood for a beautiful and long lasting finish. Ideal for wooden surfaces inside and outside the home. |
| PREPARATION Ensure surface to be oiled is smooth, clean, dry and free of contamination. For surfaces previously treated with oils or waxes clean back the surface to bare timber with fine wire wool and white spirits, working along the grain. Danish Oil is an ideal finish for use over Blackfriar Wood Dye. Ensure new or bare timber is adequately preserved prior to applying wood finishes, apply Blackfriar Goldstar Wood Preservative to untreated timbers where required. |
| APPLICATION Shake thoroughly prior to use. Apply oil liberally by brush or rag. Leave for a few minutes for the oil to absorb into the wood then wipe off any surplus. Allow the oil to dry overnight before using or recoating. When applying to new wood thin the first coat with 5% white spirit. |
| APPEARANCE Clear satin finish. |
| COVERAGE RATE Up to 14m ² /litre per coat. 4 coats recommended. |
| DRYING TIME Touch dry in 2 - 4 hours. Recoat after 16 hours and within 3 days. Drying times are based on an ambient temperature of 20°C and 50% relative humidity. Lower temperatures or higher humidity will prolong the drying and overcoating times. |
| PACK SIZES 5L, 2.5L, 1L, 500ML, 250ML. |
| CLEAN UP Take extra care as application cloths and soiled cleaning rags may self ignite without warning. Lay cloths out flat in single layers to dry, or wash out thoroughly in warm soapy water before disposal. Remove as much product as possible from application equipment before washing with white spirit. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings. |
| VOC EU limit value for this product (cat A/f): 700 g/l. This product contains max 700 g/l VOC |
| LIMITATIONS For exterior applications Blackfriar Danish Oil, as with all oils will require regular maintenance. For optimum performance, inspect the coating on a regular basis and recoat at least annually or at the first sign of breakdown. On previously sealed surfaces some oils may dry to a slight gloss. This can be reduced by gently rubbing the surface with fine wire wool and wax polish, working into the grain. For kitchen worktops use Blackfriar Kitchen Worktop Oil. |
| DISCLAIMER The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements. |
| Tor Coatings Ltd, Portobello Industrial Estate, Birtley, Chester-le-Street, County Durham, DH3 2RE. For Technical Enquiries or Material Safety Data Sheets. Contact sales on 0191 410 6611. |