



Technical Data Sheet

Blackfriar Boiled Linseed Oil

Blackfriar Boiled Linseed Oil penetrates deep into wood, providing an attractive ruby hue with a light gloss finish. Can be used inside and out and is ideal for most bare woods apart from oak. It can also be used for softening glazing putty.

Performance characteristics –

- Interior and exterior use.
- Nourishes and protects wood.
- Penetrates deep into wood.
- Light gloss.
- Water resistant.
- Suitable for most woods.

Preparation - Ensure surface to be oiled is smooth, clean, dry and free of contamination. For surfaces previously treated with oils or waxes clean back the surface to bare timber with fine wire wool and white spirit, working along the grain.

Application - Ensure the product is thoroughly shaken prior to use. Apply oil liberally by brush or rag. Leave for a few minutes for the oil to absorb into the wood then wipe off any surplus. Allow the oil to dry overnight before using or recoating. When applying to new wood thin the first coat with 10% white spirit.

Thinning - Maximum 10% white spirit.

Limitations - If used on exterior projects regular maintenance will be required to keep the wood nourished. On previously sealed surfaces some oils may dry to a slight gloss. This can be reduced by gently rubbing the surface with fine wire wool and wax polish, working with the grain. Not suitable for use on oak.

Coverage - Up to 10m² per litre per coat. Will depend upon porosity of the wood.

Drying Time - 12 hours. Drying times are based on an ambient temperature of 20°C and 50% relative humidity. Lower temperatures or higher humidity will prolong the drying and overcoating times.

Clean Up - Take extra care as application cloths and soiled cleaning rags may self ignite without warning. Lay cloths out flat in single layers to dry, or wash out thoroughly in warm soapy water before disposal. Remove as much product from application equipment as possible before washing with white spirit. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

Storage - Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight.

Keep out of reach of children.

Read label before use.

If medical advice is needed, have product container or label at hand.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

EU limit values: 150g/l (2007) 130g/l (2010.) This product contains a maximum of 100g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.