



Technical Data Sheet

Blackfriar Danish Oil

Blackfriar Danish Oil penetrates deep into the wood for a beautiful and long lasting finish. Ideal for wooden surfaces inside and outside the home.

Performance characteristics –

- Interior and exterior use.
- Satin finish.
- Penetrates deep into wood.
- Nourishes and protects wood.
- For all hard and soft woods.

Preparation - Ensure surface to be oiled is smooth, clean, dry and free of contamination. For surfaces previously treated with oils or waxes clean back the surface to bare timber with fine wire wool and white spirit, working along the grain. Danish Oil is an ideal finish for use over Blackfriar Wood Dye.

Application - Shake thoroughly prior to use. Apply oil liberally by brush or rag. Leave for a few minutes for the oil to absorb into the wood then wipe off any surplus. Allow the oil to dry overnight before using or recoating. When applying to new wood thin the first coat with 5% white spirit.

Thinning - Maximum 5% white spirit.

Limitations - For exterior applications Blackfriar Danish Oil, as with all oils will require regular maintenance. For optimum performance, inspect the coating on a regular basis and recoat at least annually or at the first sign of breakdown. On previously sealed surfaces some oils may dry to a slight gloss. This can be reduced by gently rubbing the surface with fine wire wool and wax polish, working with the grain. For kitchen worktops use Blackfriar Kitchen Worktop Oil.

Coverage - Up to 14m² per litre per coat. 4 coats recommended.

Drying Time - Touch dry in 2 - 4 hours. Recoat after 16 hours and within 3 days. Drying times are based on an ambient temperature of 20°C and 50% relative humidity. Lower temperatures or higher humidity will prolong the drying and overcoating times.

Clean Up - Take extra care as application cloths and soiled cleaning rags may self ignite without warning. Lay cloths out flat in single layers to dry, or wash out thoroughly in warm soapy water before disposal. Remove as much product from application equipment as possible before washing with white spirit. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

Storage - Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight.

Warning

Contains: Naphtha (petroleum), hydrotreated heavy.

Flammable liquid and vapour.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

Keep out of reach of children.

Read label before use.

If medical advice is needed, have product container or label at hand.

Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

Avoid breathing vapour. Wear protective gloves: Nitrile rubber (EN 374).

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention.

Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, 4,5-dichloro-2-octyl-2H-isothiazol-3-one, neodecanoic acid,

cobalt salt and 2-butanone oxime. May produce an allergic reaction.

Repeated exposure may cause skin dryness or cracking.

EU limit values: 700g/l (2007) 700g/l (2010.) This product contains a maximum of 700g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.