

# BLACKFRIAR PAINTS LTD

## TECHNICAL DATA SHEET

### BF072 Blackfriar Button Polish.

Revision date: 12/11/13
-------------------------------

<u>Product Information</u>	<u>Technical Spec</u>	<u>Recommended Spreading Rate</u>
<p style="text-align: center;"><b><u>Description</u></b></p> <p>A high quality French Polish based on Button shellac.</p> <p style="text-align: center;"><b><u>Usage/purpose</u></b></p> <p>For use on all new, dyed or previously French polished woods especially furniture, tables, ornaments etc.</p> <p style="text-align: center;"><b><u>Characteristics</u></b></p> <p>A smooth high gloss finish that brings out the natural beauty of wood.</p> <p style="text-align: center;"><b><u>Finish</u></b></p> <p>Multiple coats will provide a high gloss finish.</p> <p style="text-align: center;"><b><u>Colour(s)</u></b></p> <p>Pale to mid brown</p> <p style="text-align: center;"><b><u>Packaging</u></b></p> <p>125ml</p> <p><b><u>Disclaimer;</u></b> The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements</p>	<p style="text-align: center;"><b><u>Composition</u></b></p> <p>Based on high quality Button Shellac and Methylated Spirit.</p> <p style="text-align: center;"><b><u>Properties</u></b></p> <p>VOC Content: EU Limit (cat A/f): 700 g/L Product contains max 700g/L</p> <p style="text-align: center;"><b><u>Performance</u></b></p> <p>Gives a deep superb glossy appearance suitable for antiques etc. Not recommended for areas of high wear and tear. For interior use only.</p> <p style="text-align: center;"><b><u>Surface Preparation</u></b></p> <p>Ensure the substrate to be polished is sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease, polish etc). If preparing a surface which, has been previously waxed polished <u>always</u> degrease prior to sanding.</p> <p style="text-align: center;"><b><u>Application Method</u></b></p> <p>Ensure products are thoroughly shaken prior to use. Apply using a rubber in circular motions. Do not allow the rubber to dry out. Build up coats until the required finish is obtained.</p> <p><b>For Technical Enquiries or Material Safety Data Sheets. Contact Sales on 0191 4113146</b></p>	<p>Dependant on absorbency of the wood</p> <p style="text-align: center;"><b><u>Thinning</u></b></p> <p>Up to 10% with Methylated Spirit.</p> <p style="text-align: center;"><b><u>Drying Time</u></b></p> <p>Touch dry in 15-30 mins Recoat after 1 hour under normal conditions (20°C 50% r/h).</p> <p style="text-align: center;"><b><u>Cleaning</u></b></p> <p>Clean application equipment or spills with Methylated Spirit</p> <p style="text-align: center;"><b><u>Limitations</u></b></p> <p>For interior use only. Not resistant to heat or stains.</p> <p style="text-align: center;"><b><u>Environmental Info.</u></b></p> <p>Dangerous for the environment</p> <hr/> <p>Paint Product UN No. 1263.</p> <hr/> <p><b>Tor Coatings Ltd.</b> <b>Portobello Industrial Est,</b> <b>Birtley</b> <b>Chester-le Street</b> <b>County Durham</b> <b>DH3 2RE</b></p>