



# Technical Data Sheet

## Blackfriar Quick Drying Radiator Paint

A non-yellowing, quick drying radiator paint suitable for use on oil or water filled radiators, pipework and storage heaters. Heat resistant to 150°C.

### Performance characteristics –

- Non-yellowing.
- Quick drying.
- Heat resistant to 150°C.
- Interior use.
- Suitable for oil or water radiators.

**Preparation** - Ensure surface to be coated is clean, dry, sound and free from wax, grease or any other contamination. Previously painted surfaces in sound condition should be finely abraded and degreased prior to direct application of Blackfriar Quick Drying Radiator Paint. Remove any rust and abrade back to a clean bright surface before priming with Blackfriar Multi-Surface Primer. Coat new or bare areas with Blackfriar Multi-Surface Primer.

**Application** - Stir thoroughly prior to use with a broad stirrer. The product may be applied by brush, roller or spray. If brushing, use a good quality soft brush, apply with light strokes finishing off in one direction. Leave to dry for one hour then turn the radiator on for one hour. Allow to cool then apply another coat if required following the same procedure. If spraying, the product may be thinned up to 10% with water if needed.

**Thinning** - Maximum 10% water.

**Limitations** - Do not use under cold (less than 10°C), damp or humid conditions. Do not apply to warm or hot surfaces. Protect from water or steam for 2-3 days after application. Avoid using harsh cleaning agents on the finish.

**Coverage** - Up to 14m<sup>2</sup> per litre per coat.

**Drying Time** - Touch dry in 1 hour. Heat radiator between

coats.

**Clean Up** - Remove as much product as possible from application equipment before washing with water. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

**Storage** - Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight.

Keep out of reach of children.

Read label before use.

If medical advice is needed, have product container or label at hand.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Safety data sheet available on request.

EU limit values: 140g/l (2007) 140g/l (2010.) This product contains a maximum of 140 g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.