



# Technical Data Sheet

## Blackfriar Vinyl Matt Emulsion

A high quality, quick drying, vinyl matt emulsion paint that provides excellent obliteration. Ideal for walls, ceilings and most surfaces including plaster, brickwork, cement and concrete.

### Performance characteristics –

- Smooth, vinyl matt finish.
- High opacity.
- Quick drying.
- Interior use.
- For walls and ceilings.

**Preparation** - Ensure surface to be coated is clean, dry, sound and free from wax, grease or any other contamination. Treat any mould growth with Blackfriar Anti-Mould Solution, which should be allowed to dry completely before applying Blackfriar Vinyl Matt Emulsion. Where necessary prime any new or bare areas with the appropriate Blackfriar primer. Chalky or powdery surfaces should be primed with Blackfriar Stabilising Solution.

**Application** - Stir thoroughly prior to use with a broad stirrer. The product may be applied by brush, roller or spray. The product may be thinned up to 10% with water if spraying. If you are applying by brush, roller or pad to new or absorbent surfaces the first coat should be thinned up to 25% to seal the surface.

**Limitations** - Do not use under cold (less than 10°C), damp or humid conditions.

**Coverage** - Up to 14m<sup>2</sup> per litre per coat.

**Drying Time** - Touch dry in 1 - 2 hours. Recoat after 4 hours. Drying times are based on an ambient temperature of 20°C and 50% relative humidity. Lower temperatures or higher humidity will prolong the drying and overcoating times.

**Clean Up** - Remove as much product as possible from application equipment before washing with water. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

**Storage** - Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight.

Keep out of reach of children.

Read label before use.

If medical advice is needed, have product container or label at hand.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains: 2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl) triethanol. May produce an allergic reaction.

Safety data sheet available on request.

EU limit values: 400g/l (2007) 30g/l (2010.) This product contains a maximum of 30g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.