

BLACKFRIAR PAINTS

TECHNICAL DATA SHEET

BF009 Blackfriar Exterior Varnishes

Review date:
21/07/11

<u>Product Information</u>	<u>Technical Spec</u>	<u>Recommended Spreading Rate</u>
<p style="text-align: center;"><u>Description</u></p> <p>A range of high performance exterior varnishes.</p> <p style="text-align: center;"><u>Usage/purpose</u></p> <p>Primarily for use on exterior joinery.</p> <p style="text-align: center;"><u>Characteristics</u></p> <p>Very Good UV resistance when used with Blackfriar UV Wood Primer.</p> <p style="text-align: center;"><u>Finish</u></p> <p>BF0090001 Gloss BF0090002 Satin</p> <p style="text-align: center;"><u>Colour(s)</u></p> <p>Gloss and Satin Clear (give slight yellow hue).</p> <p style="text-align: center;"><u>Packaging</u></p> <p>250ml, 500ml, 1litre, 2.5litre. Larger sizes may be available on request dependant on volume required</p> <p><u>Disclaimer;</u> The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.</p>	<p style="text-align: center;"><u>Composition</u></p> <p>Based on a urethane alkyd resin, UV absorber and low aromatic white spirits.</p> <p style="text-align: center;"><u>Properties</u></p> <p>EU limit value for this product (cat A/e): 400 g/l. This product contains max 400 g/l VOC</p> <p style="text-align: center;"><u>Performance</u></p> <p>A weather resistant, tough & flexible, water repelling coating for new or bare wood.</p> <p style="text-align: center;"><u>Surface Preparation</u></p> <p>Ensure the substrate to be coated is sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease, polish etc). Remove old varnish completely with Blackfriar Paint and Varnish Remover. If sanding ensure all debris is removed before priming with Blackfriar UV Wood Primer prior to applying varnishes.</p> <p style="text-align: center;"><u>Application Method</u></p> <p>Brush or Spray Ensure products are thoroughly stirred with a broad stirrer. Apply a minimum of two coats for exterior protection. Always apply over Blackfriar UV Wood Primer</p> <p style="text-align: center;">For Material Safety Data Sheets Technical Enquiries, contact Sales on 0191 4106611</p>	<p style="text-align: center;"><u>Drying Time</u></p> <p>12-14m²/l per coat. Two coats required.</p> <p style="text-align: center;"><u>Cleaning</u></p> <p>Clean application equipment or spills with white spirit or Blackfriar Brush Cleaner</p> <p style="text-align: center;"><u>Limitations</u></p> <p>Clear varnishes are not as durable as pigmented varnishes or stains. Inspect Clear varnishes <u>regularly</u> and maintain immediately any sign of breakdown occurs.</p> <p style="text-align: center;"><u>Environmental Info.</u></p> <p>Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic Flammable</p>
		<p>Touch dry in 4-6 hours Recoatable after 16 hours under normal conditions (10°C 50% RH).</p>
		<p>Paint Product UN No. 1263.</p>
		<p>Tor Coatings Ltd Portobello Ind Estate Birtley Chester le Street Co Durham Tel; 0191 4106611 Fax; 0191 4920125</p>