

BLACKFRIAR PAINTS LTD. TECHNICAL DATA SHEET

Revision Date:
15/03/2011

AE022 Blackfriar Line Marking Paint Aerosol.

<u>Product Information</u>	<u>Technical Spec</u>	<u>Recommended Spreading Rate</u>
<p style="text-align: center;"><u>Description</u></p> <p>A quick drying line marking paint supplied ready for use in handy 750ml aerosol pack.</p> <p style="text-align: center;"><u>Usage/purpose</u></p> <p>Ideal for marking factory floors, car parks step edges and general delineation.</p> <p style="text-align: center;"><u>Characteristics</u></p> <p>Quick drying with good light and colour fastness.</p> <p style="text-align: center;"><u>Finish</u></p> <p>Semi Gloss</p> <p style="text-align: center;"><u>Colour(s)</u></p> <p>White, Yellow, Red, Blue, Green & Black</p> <p style="text-align: center;"><u>Packaging</u></p> <p>750ml Aerosol</p> <p><u>Disclaimer;</u> The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.</p>	<p style="text-align: center;"><u>Composition</u></p> <p>Based on a high quality blend of alkyd resins coupled with carefully selected pigments and extenders to give good light fastness and durability.</p> <p style="text-align: center;"><u>VOC</u></p> <p>570 g/litre</p> <p style="text-align: center;"><u>Performance</u></p> <p>Interior or exterior Use.</p> <p style="text-align: center;"><u>Surface Preparation</u></p> <p>Ensure the substrate to be painted is sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease etc).</p> <p style="text-align: center;"><u>Application Method</u></p> <p>Supplied ready for use. Aerosol can will also fit most linemarking machines</p> <p>For Technical Enquiries Material Safety Data Sheets. Contact Sales on 0191 4106611</p>	<p style="text-align: center;"><u>Drying Time</u></p> <p>Dry in 10-20 mins under normal conditions (20°C 50% RH).</p> <p style="text-align: center;"><u>Cleaning</u></p> <p>Use xylene or paint thinners</p> <p style="text-align: center;"><u>Limitations</u></p> <p>Avoid application in damp, wet or very windy conditions.</p> <p style="text-align: center;"><u>Environmental Info.</u></p> <p>Over 75% of local authorities collect aerosols in their can banks along with drinks cans or through their kerbside collection schemes.</p> <p>To find out if your local authority is amongst them, contact your local recycling officer</p>
		<p>One can covers approximately 6-8m²</p>
		<p>Paint Product UN No. 1950.</p>
		<p>Tor Coatings Ltd. Portobello Industrial Est, Birtley Chester-le Street County Durham DH3 2RE</p>