

BLACKFRIAR PAINTS LTD
TECHNICAL DATA SHEET
BF0520003 **Blackfriar Satin Black Paint.**

Revision date: 17/03/2010

Product Information

Description

An attractive hardwearing black satin finish for metal and wood.

Usage/purpose

Ideal for old beams, wrought ironwork, gates, railings, doors, skirting, steel fabrications etc. Interior and exterior applications.

Characteristics

A liquid paint with a mild odour.

Finish

Satin Finish

Colour(s)

Black

Packaging

125ml, 250ml, 500ml, 1litre, 2.5litre. Larger sizes may be available on request dependent on volume required.

Disclaimer;

The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements

Technical Spec

Composition

Based on a blend of black and anti-corrosive pigments with long oil and urethane modified alkyd resins in low aromatic white spirits.

VOC

EU limit value for this product (cat A/i): 500 g/l (2010). This product contains max 500 g/l VOC

Performance

An attractive black paint ideal for use inside or outside. Exhibits some anti-corrosive properties.

Surface Preparation

Ensure the substrate to be painted is sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease etc). Remove all signs of rust to a clean bright surface. Prime new and bare areas with the appropriate Blackfriar Primer.

Application Method

Brush, Roller, Spray.
Ensure products are thoroughly stirred with a broad stirrer prior to use.
For best results apply a minimum of two coats.

**For Technical Enquiries,
Material Safety Data Sheets
Telephone Sales on 0191 4106611**

Recommended Spreading Rate

13m²/ltr

Thinning

Up to 10% with white spirit

Drying Time

Touch dry in 2-4 hours
Recoat after 16 hours under normal conditions (20°C 50% RH).

Cleaning

Clean application equipment or spills with white spirit or Blackfriar Brush Cleaner

Limitations

Stir thoroughly to ensure matting agent is fully incorporated before use

Environmental Info.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic
Flammable

Paint Product
UN No. 1263.

**Tor Coatings Ltd.
Portobello Industrial Est,
Birtley
Chester-le Street
County Durham
DH3 2RE**