

BLACKFRIAR PAINTS LTD

TECHNICAL DATA SHEET

BF068 Blackfriar Water-Based Paint Remover.

Revision
Date:
09/01/07

<u>Product Information</u>	<u>Technical Specification</u>	<u>Recommended Spreading Rate</u>
<u>Description</u> A high performance water based stripping system, self-neutralising. Does not discolour wood.	A blend of Benzyl Alcohol, surfactants and evaporation retardants.	Up to 4 square metres per litre per coat. Depends on number of coats and types of paint to be removed.
<u>Usage/purpose</u> A stripper that will remove emulsions, gloss, French polish, polyurethane varnish and cellulose finishes.	<u>Properties</u> VOC Content: 0 g/litre	<u>Thinning</u> Do not thin
<u>Characteristics</u> Non-caustic formulation. Good holding properties on vertical surfaces.	<u>Performance</u> Effective paint removal. Can strip multiple coats of paint in one application.	<u>Drying Time</u> Not applicable
<u>Finish</u> Not a Finish	<u>Surface Preparation</u> Ensure surfaces to be stripped are dry. Remove wax or greasy deposits before use. Scouring/abrading the paint surface prior to use will speed up the action of the Water Based Paint Remover. Protect adjacent surfaces from splashes.	<u>Cleaning</u> Clean application equipment or spills with water.
<u>Colour(s)</u> White/ milky	<u>Application Method</u> Brush. Apply a generous coat to the surface to be stripped. Leave for 45-60 minutes (longer if multiple coats to be removed). Scrape softened residue from surface. Repeat until all coatings removed. Use fine grade wire wool to aid removal on intricate surfaces such as mouldings. On Two-pack or Stoved finishes cover with plastic sheeting and leave for a longer period of time.	<u>Limitations</u> Do not allow to dry out during treatment. If scraping is attempted too soon after application the treatment will not have had time to soften the layers of paint. Do not use over Nylon, Vinyl, Perspex or plastic surfaces.
<u>Packaging</u> 1litre. Larger sizes may be available on request dependent on volume required.		<u>Environmental Info.</u> Water based.
<u>Disclaimer;</u> The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements	For Technical Enquiries, Material Safety Data Sheets Telephone Sales on 0191 4106611	Tor Coatings Ltd. Portobello Industrial Est, Birtley Chester-le Street County Durham DH3 2RE