

**BLACKFRIAR PROFESSIONAL
TECHNICAL DATA SHEET**

BF205 ANTI CLIMB PAINT
PIGMENTED PETROLEUM WAX
<p>EXTERIOR USE NONE DRYING CONTAINS TRACE STAIN</p>
<p align="center">BLACKFRIAR PROFESSIONAL ANTI CLIMB PAINT</p> <p>Blackfriar Professional Anti Climb Paint is a thick non-drying coating for parapets, downcomers, pipes etc for use as a deterrent to would be intruders, burglars and vandals.</p>
<p>PREPARATION</p> <p>Ensure the surface to be painted is sound, clean and dry. Scrape off any old or flaking paint until you have a firm surface. Porous surfaces should be sealed with Blackfriar Professional Solvent Based Floor Sealer. Bare steel after cleaning should be given one coat of Blackfriar Red Oxide Zinc Phosphate Primer. Plastic downcomers should be roughened by rubbing with medium grade abrasive paper.</p>
<p>APPLICATION</p> <p>Apply liberally with a stiff brush or lambs wool mitt. On bare or new surfaces first apply Blackfriar Professional Solvent Based Floor Sealer followed by 1 coat of Blackfriar Professional Anti Climb Paint. On previously painted surfaces apply 1 coat as required. Only apply to areas not subject to legitimate daily contact usually limited to areas above 6 feet. Blackfriar Professional Anti Climb works best on surfaces or in areas below 35°C. The product will attract a surface layer of dust but this will not affect performance.</p>
<p>APPEARANCE</p> <p>Semi Matt Black, Mid Grey, Tile Red, Green.</p>
<p>COVERAGE RATE</p> <p>2m²/L</p>
<p>DRYING TIME</p> <p>Does not dry.</p>
<p>PACK SIZES</p> <p>5L, 2.5L, 1L</p>
<p>CLEAN UP</p> <p>Remove as much product from application equipment as possible before washing with White Spirits. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings.</p>
<p>VOC</p> <p>EU limit value for this product (cat A/i): 500 g/l. This product contains max 500 g/l VOC</p>
<p>DISCLAIMER</p> <p>The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.</p>
<p>Tor Coatings Ltd, Portobello Industrial Estate, Birtley, Chester-le-Street, County Durham, DH3 2RE. For Technical Enquiries or Material Safety Data Sheets. Contact sales on 0191 410 6611</p>