BLACKFRIAR A TRADITION OF EXCELLENCE SINCE 1894

# **Technical Data Sheet**

# Blackfriar Professional Line-Marking Paint

A quick drying and durable paint which provides clear, long-lasting markings on concrete, tarmac and painted surfaces. Ideal for indoor and outdoor use on kerbs, factory floors, car parks, schools and public areas.

#### Performance characteristics -

- 30 minute drying time.
- Solvent-based with excellent resistance to abrasion and cleaning products.
- Ideal for domestic, commercial and industrial traffic areas.
- Indoor and outdoor use.
- Brush or roller application.

### Preparation

First ensure the surface to be painted is clean, thoroughly dry, and free from powdery deposits. If you are marking new concrete, make sure its has had at least 6 months to dry out before coating.

### Application

Before use, stir the paint well with a broad stirrer. Apply by brush, roller or line marking machine. If applying by brush, apply a generous, even coat with the minimum of brushing. For best results, apply 2 coats. Do not apply this paint in damp, wet, or excessively hot conditions. If necessary, this paint may be thinned with up to 10% Blackfriar Professional Degreaser / Cleaner – it must not be thinned with white spirit. Please note that Blackfriar Professional Line Marking Paint is not suitable for use as a floor paint, only for marking lines.

## **Drying Time**

30 minutes in good conditions.

## **Covering Capacity**

Approximately 6m<sup>2</sup>/litre per coat depending on the porosity of the surface.

#### **Clean Up**

Remove as much product from application equipment as possible before washing with Blackfriar Professional Degreaser / Cleaner. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings.

### Warning

#### Contains: Xylene

Flammable liquid and vapour.

Harmful in contact with skin. Causes skin irritation.

Harmful if inhaled.

Keep out of reach of children.

Keep away from heat/sparks/open flame/hot surfaces. - No smoking.

Use only outdoors or in a well ventilated area.

Wear protective gloves/protective clothing/eye protection/ face protection.

IF ON SKIN: Gently wash with plenty of soap and water. Dispose of contents/container in recognised waste collection point.

VOC - EU limit value for this product (cat A/j): 500 g/l. This product contains max 500 g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.

Manufactured in the UK by Blackfriar Paints - A division of Tor Coatings Ltd. Portobello Industrial Estate, Birtley, Chester-le-Street, County Durham, DH3 2RE. For technical advice please tel: +44 (0) 191 411 3146 or e-mail: enquiries@tor-coatings.com • www.blackfriar.co.uk